Postal Rate Chart

Effective October 202

For more detailed pricing information, go to www.usps.com/business/prices.htm. Find a transit time map at https://ribbs.usps.gov/modernservicestandards/ssmaps/find_map.cfm.

FIRST CLASS MAIL (1-3 days standard transit time from 58103 in the Continental US)						
	POSTCAF	RDS L	ETTERS	FLATS		
Metered						
	0.51		0.63			
Non-Automation (und	der 1 oz)					
Single Piece	0.51		0.66	1.35		
Automation						
	0.335 - 0.	388 0.4	98 - 0.561	0.498 - 1.35		
MARKETING MAIL (3-8 days standard transit time from 58103 in the Continental US)						
	LETTERS (3.	LETTERS (3.5 oz. or less)		FLATS (4.0 oz. or less)		
Non-Automation (Machi	nable) Standard	Non-Profit	Standard	Non-Profit		
	0.328 - 0.387	0.173 - 0.232	0.614 - 1.007	0.389 - 0.782		
Automation						
	0.291 - 0.381	0.136 - 0.226	0.518 - 0.976	0.293 - 0.751		
Carrier Route (Saturation)			EDDM			
			None - 0.301 NDC - 0.230 SCF - 0.210 DDU - 0.197	None - 0.211 NDC - 0.140 SCF - 0.120 DDU - 0.107		

NOTES

EDDM Retail

Minimum of 200 pieces to use an indicia.

Minimum of 500 pieces for First Class automated rates.

Minimum of 200 for Standard automated rates.

Rectangle shape with aspect ratio (length divided by height) between 1.3 and 2.5.



www.knightprinting.com • 701.235.1121 • 888.526.1121

	O DADED O	TANDARDS.
MMMMM	II DADED S	
1417211211		IAINDAINDO

	MINIMUM	MAXIMUM				
Presorted or Automation 1st Class Postcard						
Height	3.5″	6″				
Length	5″	9″				
Thickness	0.0090″	0.0160″				
Letters						
Height	3.5″	6.125"				
Length	5″	11.5″				
Thickness	0.0090″	0.25″				
Folded Self Mailers						
Height	3.5″	6″				
Length	5″	10.5″				
Thickness	0.0090"	0.25"				
# of Panels (counting both sides)	2	12				
Flats						
Height	5″	12″				
Length	6″	15″				
Thickness	0.0090″	0.75″				

Address Block Area for Letters

Minimum inkjet area needed 3.75" L x 2.75" H Barcode & Postal markings area needed 4.75" L x .625" H Address block needs to be 0.625" from bottom of mail piece.

Address Block needs to be on top half of mail piece with bound edge to the right and 1/8" clearance on all sides.